



PART ROOF FRAMING PLAN SEQ.-D
 (ALL EL. INDICATES T.O.S (U.N.O))

- NOTES:-
1. ALL WF BEAM WITH DOUBLE SHEAR CONN. FRAMED INTO COL. USE $\frac{3}{4}$ A325 N BOLTS.
 2. ALL SINGLE SHEAR PLATE CONNECTION OF BEAM USE $\frac{3}{4}$ A325 X BOLTS U.N.O
 3. W8x31, W8x40 & W10x33 @ DOUBLE SHEAR CONNECTION USE $\frac{3}{4}$ A325 X BOLTS U.N.O
 4. FOR W16x57 & W14x48 @ MOMENT PLATE CONN. USE 8 NO. $\frac{3}{4}$ A490 X BOLTS
 5. FOR ALL OTHER BEAMS @ MOMENT PLATE CONN. USE $\frac{3}{4}$ A325 X BOLTS.
 6. FOR SECTIONS REFERENCE DWG. NO E16
 7. FOR LINTEL MARKING REF. SEPARATE DWG.
 8. ALL HAMBRO JOIST SPACING VERIFY WITH HAMBRO JOIST DWG.
 9. (S) INDICATES SLOPED BEAM
 10. FOR ALL WF BEAM TO TS COL. FIELD WELDED MOMENT CONN. REF. ERECTION DWG. NO. E17

REV.	DATE	DESCRIPTION
A		ISSUED FOR FIELD USE

Detailer: D & A TECHNICAL SERVICES, INC. LAUREL, MARYLAND PH: 3012725593 Fax:2402355302		
ISSUE FOR	DATE	Rel. Dwg. S2.1B & S5.1 TO S5.3
APPROVAL	Project:	Dwg. Description PART ROOF FRAMING PLAN (SEQ-D)
APPROVAL	Location:	
	Customer:	
	Arch:	
	Detailed By:	Date:
	Checked By:	Date:
	Job No.	Dwg. No. E18
	Rev.	

